## **BAD305 Portable Searchlight**

- Explosion protection to
  - -CENELEC
  - -IEC
  - -NEC
- Can be used in

Zone 1 and Zone 2

Zone 21 and Zone 22

Class I, Zone 1 and Zone 2

Class I, Division 1, Groups A, B, C, D

- Safe and reliable: the product with reliable explosion-proof performance, can safely and reliably work in various combustible areas, the battery is equipped with PTC thermistor and temperature fuse; double-protected circuit, safety performance enhanced.
- Efficient and energy-saving: memory-free battery, with long service life, low auto-discharge rate, economic and environmental friendly, solid efficient LED lamp, low energy consumption and long service life.
- Water-proof and damage-proof: the enclosure is made of imported alloy with high strength, excellent strong impact resistant performance, unique sealing type, with very good water-proof performance.
- 🧼 Anti-strong interference: scientific module driving circuit, strong performance of anti-shock and anti-electromagnetic interference.
- Heat resistant: LED radiator and battery are effectively isolated, which improves the stability of the light.
- Intelligent control: pulse dimming technology, strong light and working light can be changed at random, with battery detection indicator, which can detect the working condition at any time, intelligent charger is with protection circuit.
- 🧼 Portable and flexible: small volume, light weigh, several types of handling like portable and on shoulder, meet different working requirement.



**Explosion protection** ( II 2 G Ex d ia IIC T6 Gb Gas explosion protection II 2 D Ex tb IIIC T80℃ Db IP68 **Dust explosion protection** LCIE 13 ATEX : IECEx Certificates

Conformity to standards EN 60079-0: 2009, EN 60079-1: 2007, EN 60079-11: 2007, EN 60079-31: 2009 IEC 60079-0: 2011, IEC 60079-1: 2007, IEC 60079-11: 2006, IEC 60079-31: 2008

Rated voltage 14.8V Rated capacity 2Ah

Lamp(LED) Rated power 9W / 3W 900mA Current of strong light

Continuous working time Strong light

≥8h Working light ≥16h Charge time

Service life of battery about 1000 times cycling

Degree of protection **IP68** Weight 790g

Zones 1&2; 21&22



2/107 General Catalogue 01.01.2013 http://www.waromgroup.com