

## **BAD309E Searchlight**

- Explosion protection to
  - -CENELEC
  - -IEC
  - -NEC
- Can be used in

Zone 2

Zone 21 and Zone 22

Class I, Zone 2

Class I, Division 2, Groups A, B, C, D

- Safe and reliable: the product with good explosion-proof performance and antistatic effect, can safely and reliably work in various combustible areas.
- Efficient and energy-saving: LED solid lamp, low energy consumption, high luminous efficacy, long service life, maintenance free and no subsequent usage cost, memory-free battery is recyclable, pollution-free.
- Water-proof and damage-proof: the light adopts whole-sealing craft, applicable in damp and severe atmosphere, special alloy enclosure makes sure the light can resist strong shock and impact.
- Intelligent control: the light is with two kinds of working modes: strong light and working light, switch is controlled by intelligent chip, the strong light and weak light can be changed at random, single-chip control; with battery display and special protection circuit, with protection function of anti-over charging, over discharging and short circuit, reliably protect the battery and prolong the service life.
- Convenient and durable: unique lamp cap; lighting angle can be adjusted within the scope of -45-55, no lighting dead angle (lighting range of strong light: 800m, effective distance: 300m, suitable for long-distance searching and lighting in large area of close range), light weight, portable type, horizontal type, hang type, magnetic absorption, etc, convenient to use; the switch is with anti-incorrect operation function.

(E) II 3 G Ex nR IIC T6 Gc

LCIE 12 ATEX

12V

4Ah

9W / 3W

100000h

≥8h

≥18h

≥8h

II 2 D Ex tb IIIC T80℃ Db IP66

EN 60079-0: 2009, EN 60079-15: 2010, EN 60079-31: 2009 IEC 60079-0: 2007, IEC 60079-15: 2010, IEC60079-31: 2008



## **Technical data**

## Searchlight BAD309E

	!		tection
EXD	INSINN	nro	TOCTION

Gas explosion protection

Dust explosion protection

Certificates

Conformity to standards

Rated voltage Rated capacity

Lamp(LED)

Rated power
Average service life

Continuous working time

Strong light
Working light
Charging time

Service life of battery about 1000 times cycling

Degree of protection IP66
Weight 1.9kg

Zones 2; 21&22